



LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.65V I:0.1225A P:10.994W PF:0.4069 Freq:50.00Hz Lamp Flux:802.651x1 lm		
NAME: 6557	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: NORDECOR	SUR.:	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 73.01 lm/W			
MODEL		I _{max} (cd)	2347	S/MH (C0/180)	0.52
NOMINAL POWER(W)		LOR (%)	100.0	S/MH (C90/270)	0.46
RATED VOLTAGE (V)	--	TOTAL FLUX(lm)	802.65	η UP,DN (C0-180)	0.0,53.7
NOMINAL FLUX(lm)	802.651	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,46.3
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	--	η down (%)	100.0	CIBSE SHR MAX	0.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature:25.3°C
Operators:
Test Date:2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1757	1844	1884	1886	1873	1745	1647	1648	0~ 10	194.8	194.8	24.3,24.3
20	594.6	715.3	769.9	776.1	730.3	561.1	488.6	493.3	10~ 20	326.1	520.9	64.9,64.9
30	130.3	145.3	160.7	164.3	150.2	123.1	117.7	115.5	20~ 30	139.8	660.7	82.3,82.3
40	71.94	69.48	75.47	77.20	70.64	68.62	67.08	65.74	30~ 40	59.19	719.8	89.7,89.7
50	44.46	42.86	46.13	46.21	42.98	42.37	38.28	39.27	40~ 50	43.75	763.6	95.1,95.1
60	17.13	17.34	18.29	18.12	16.55	15.81	14.71	15.24	50~ 60	25.38	789.0	98.3,98.3
70	4.907	5.398	5.579	5.304	4.874	4.306	4.131	4.340	60~ 70	9.617	798.6	99.5,99.5
80	1.745	1.918	1.982	1.887	1.743	1.558	1.475	1.542	70~ 80	3.189	801.8	99.9,99.9
90	0.0636	0.0742	0.1320	0.1147	0.0655	0.0703	0.0694	0.0723	80~ 90	0.8647	802.7	100,100
100									90~100			
110									100~110			
120									110~120			
130									120~130			
140									130~140			
150									140~150			
160									150~160			
170									160~170			
180									170~180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 743.46 lm

%lum = 92.6%

%lamp = 92.6%

Conical surface Flux(120deg): 788.98 lm


%lum = 98.3%

%lamp = 98.3%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: 10.0deg/s
 Temperature:25.3℃
 Operators:
 Test Date:2023-11-06

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES




LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	6746	8953
80	8037	9129
75	9235	9992
70	11478	13049
65	18394	19187
60	27404	29263
55	41221	42561
50	55332	57411
45	66143	68782

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature: 25.3°C
Operators:
Test Date: 2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.09	1.07	1.09	1.07	1.06	1.05	1.04	1.02	1.02	1.00	.99	.98	.97	.96	.95
2.0	1.05	1.01	.98	1.03	.00	.97	.00	.97	.95	.97	.95	.93	.94	.93	.91	.89
3.0	.99	.95	.91	.98	.94	.90	.95	.92	.89	.93	.90	.87	.90	.88	.86	.85
4.0	.94	.89	.85	.93	.88	.85	.91	.87	.84	.89	.85	.83	.87	.84	.82	.80
5.0	.89	.84	.80	.88	.84	.80	.87	.82	.79	.85	.81	.79	.83	.80	.78	.77
6.0	.85	.80	.76	.84	.79	.76	.83	.79	.75	.82	.78	.75	.80	.77	.75	.73
7.0	.81	.76	.73	.81	.76	.72	.80	.75	.72	.78	.75	.72	.77	.74	.71	.70
8.0	.78	.73	.70	.78	.73	.69	.76	.72	.69	.76	.72	.69	.75	.71	.69	.67
9.0	.75	.70	.67	.75	.70	.67	.74	.69	.66	.73	.69	.66	.72	.69	.66	.65
10.0	.72	.67	.64	.72	.67	.64	.71	.67	.64	.70	.67	.64	.70	.66	.64	.63



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature:25.3℃
Operators:
Test Date:2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.163	.093	.029	.156	.089	.028	.144	.082	.026	.132	.076	.024	.122	.071	.023		
2.0	.154	.084	.026	.148	.082	.025	.138	.077	.024	.128	.072	.023	.119	.067	.021		
3.0	.145	.077	.023	.140	.075	.023	.131	.071	.022	.123	.067	.021	.115	.064	.020		
4.0	.136	.071	.021	.132	.069	.020	.125	.066	.020	.118	.063	.019	.111	.060	.018		
5.0	.129	.066	.019	.125	.064	.019	.119	.062	.018	.113	.059	.018	.107	.057	.017		
6.0	.122	.061	.017	.119	.060	.017	.113	.058	.017	.108	.056	.016	.103	.054	.016		
7.0	.115	.057	.016	.113	.056	.016	.108	.055	.016	.103	.053	.015	.099	.051	.015		
8.0	.110	.054	.015	.107	.053	.015	.103	.051	.015	.099	.050	.014	.095	.049	.014		
9.0	.105	.051	.014	.103	.050	.014	.099	.049	.014	.095	.048	.014	.092	.047	.013		
10.0	.100	.048	.013	.098	.047	.013	.095	.046	.013	.091	.045	.013	.088	.044	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.170	.157	.146	.146	.135	.126	.100	.093	.087	.057	.054	.051	.018	.017	.016		
2.0	.154	.133	.115	.132	.114	.099	.090	.079	.069	.052	.046	.041	.017	.015	.013		
3.0	.140	.113	.092	.120	.098	.080	.083	.068	.056	.048	.040	.033	.015	.013	.011		
4.0	.129	.098	.075	.111	.085	.065	.076	.059	.046	.044	.035	.027	.014	.011	.009		
5.0	.119	.087	.062	.103	.075	.054	.071	.052	.038	.041	.031	.023	.013	.010	.007		
6.0	.111	.077	.052	.095	.067	.046	.066	.047	.032	.038	.027	.019	.012	.009	.006		
7.0	.104	.069	.045	.089	.060	.039	.062	.042	.028	.036	.025	.016	.012	.008	.005		
8.0	.098	.063	.038	.084	.054	.033	.058	.038	.024	.034	.022	.014	.011	.007	.005		
9.0	.092	.057	.033	.079	.050	.029	.055	.035	.021	.032	.021	.012	.010	.007	.004		
10.0	.087	.052	.029	.075	.046	.026	.052	.032	.018	.030	.019	.011	.010	.006	.004		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature:25.3℃
Operators:
Test Date:2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	20.9	21.7	21.1	21.8	22.0	21.0	21.8	21.2	22.0	22.1
3H	21.0	21.7	21.2	21.9	22.1	21.1	21.9	21.4	22.1	22.3
4H	21.0	21.7	21.2	21.9	22.1	21.1	21.9	21.4	22.1	22.3
6H	20.9	21.6	21.2	21.9	22.1	21.1	21.8	21.4	22.0	22.3
8H	20.9	21.6	21.2	21.8	22.1	21.1	21.8	21.4	22.0	22.3
12H	20.9	21.5	21.2	21.8	22.1	21.1	21.7	21.4	22.0	22.3
4H 2H	20.9	21.7	21.2	21.9	22.1	21.1	21.8	21.3	22.0	22.2
3H	21.1	21.7	21.4	22.0	22.3	21.3	21.9	21.6	22.1	22.4
4H	21.1	21.7	21.5	22.0	22.3	21.3	21.9	21.6	22.2	22.5
6H	21.1	21.6	21.5	22.0	22.3	21.3	21.8	21.7	22.1	22.5
8H	21.1	21.6	21.5	21.9	22.3	21.3	21.8	21.7	22.1	22.5
12H	21.1	21.5	21.5	21.9	22.3	21.3	21.7	21.7	22.1	22.5
8H 4H	21.0	21.5	21.4	21.9	22.2	21.2	21.7	21.6	22.0	22.4
6H	21.1	21.5	21.5	21.9	22.3	21.3	21.6	21.7	22.0	22.5
8H	21.1	21.4	21.5	21.8	22.3	21.3	21.6	21.7	22.0	22.5
12H	21.1	21.4	21.5	21.8	22.3	21.3	21.6	21.8	22.0	22.5
12H 4H	21.0	21.4	21.4	21.8	22.2	21.2	21.6	21.6	22.0	22.4
6H	21.0	21.4	21.5	21.8	22.2	21.2	21.6	21.7	22.0	22.4
8H	21.1	21.4	21.5	21.8	22.3	21.3	21.6	21.7	22.0	22.5
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 1.0 / - 1.4					+ 0.9 / - 1.3				
1.5H	+ 0.5 / - 0.8					+ 0.5 / - 0.8				
2.0H	+ 2.2 / - 2.7					+ 2.2 / - 2.6				

CIE Pub.117, 802.7 lm Total Lamp Luminous Flux Corrected (8log(F/F0) = -0.8)
Area: 0.00125 m2

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature:25.3°C
Operators:
Test Date:2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:


UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	85	78	74	84	78	74	84	78	74	70
0.80	93	86	82	92	86	82	91	85	82	78
1.00	98	92	88	97	91	87	95	91	87	83
1.25	102	96	93	101	96	92	99	95	91	87
1.50	105	100	96	104	99	96	101	97	95	90
2.00	108	103	100	106	102	99	104	100	98	92
2.50	110	106	102	108	104	101	105	102	100	94
3.00	111	108	105	109	106	104	106	104	101	95
4.00	113	110	108	111	109	107	108	106	104	97
5.00	115	112	110	112	110	109	109	107	106	98
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: 10.0deg/s
 Temperature: 25.3°C
 Operators:
 Test Date: 2023-11-06

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.463
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:


ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature:25.3°C
Operators:
Test Date:2023-11-06

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: 10.0deg/s
 Temperature:25.3℃
 Operators:
 Test Date:2023-11-06

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:


ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature: 25.3°C
Operators:
Test Date: 2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature: 25.3°C
Operators:
Test Date: 2023-11-06

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: 10.0deg/s
Temperature: 25.3°C
Operators:
Test Date: 2023-11-06

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

```

LUMINOUS DISTRIBUTION INTENSITY DATA

UNIT: cd

[illegible]

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.463
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

```