


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

DATA OF LAMP		PHOTOMETRIC DATA Eff: 57.90 lm/W			
MODEL		I _{max} (cd)	2194	S/MH(C0/180)	0.49
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	0.34
RATED VOLTAGE(V)	85-265V	TOTAL FLUX(lm)	560.19	h UP, DN(C0-180)	0.0,58.3
NOMINAL FLUX(lm)	560.193	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0,41.7
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	220	h down(%)	100.0	CIBSE SHR MAX	1.00



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.300m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum, lamp
10	1167	1376	1525	1430	1694	1147	1076	1132	0- 10	155.5	155.5	27.8, 27.8
20	246.0	556.0	842.0	546.5	558.6	257.2	369.2	267.6	10- 20	222.6	378.1	67.5, 67.5
30	46.41	105.0	113.6	154.6	90.81	75.25	43.34	59.34	20- 30	106.7	484.7	86.5, 86.5
40	23.58	25.26	54.03	27.57	28.52	22.21	27.58	21.41	30- 40	29.15	513.9	91.7, 91.7
50	17.17	17.91	21.57	19.12	20.90	16.80	17.35	15.64	40- 50	17.26	531.2	94.8, 94.8
60	10.76	12.92	16.22	13.79	14.95	12.04	12.62	10.32	50- 60	13.83	545.0	97.3, 97.3
70	5.163	8.288	9.824	8.686	9.078	6.967	6.195	5.385	60- 70	9.879	554.9	99, 99
80	2.181	2.935	0	2.891	3.603	1.896	0	1.519	70- 80	4.774	559.6	99.9, 99.9
90	1.138	0	0	0	1.147	0	0	0	80- 90	0.5551	560.2	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 523.22 lm

%lum = 93.4%

%lamp = 93.4%

Conical surface Flux(120deg): 544.98 lm

%lum = 97.3%

%lamp = 97.3%

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-08-16

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.300m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	143	0
80	126	0
75	133	257
70	151	287
65	179	310
60	215	324
55	244	331
50	267	336
45	287	343


H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

r CC	80%			70%			50%			30%			10%			0
r W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.12	1.09	1.07	1.10	1.08	1.06	1.06	1.04	1.02	1.02	1.01	.99	.98	.97	.97	.95
2.0	1.05	1.02	.99	1.03	1.00	.98	1.00	.98	.95	.97	.95	.93	.95	.93	.91	.90
3.0	.90	.95	.92	.98	.94	.91	.96	.92	.90	.93	.91	.88	.91	.89	.87	.86
4.0	.95	.90	.86	.94	.89	.86	.92	.88	.85	.90	.87	.84	.88	.85	.83	.82
5.0	.90	.86	.82	.89	.85	.82	.88	.84	.81	.86	.83	.80	.85	.82	.80	.78
6.0	.87	.82	.78	.86	.81	.78	.84	.80	.77	.83	.80	.77	.82	.79	.76	.75
7.0	.83	.78	.75	.83	.78	.75	.81	.77	.74	.80	.77	.74	.79	.76	.73	.72
8.0	.80	.75	.72	.79	.75	.72	.78	.74	.71	.78	.74	.71	.77	.73	.71	.70
9.0	.77	.72	.69	.77	.72	.69	.76	.72	.69	.75	.71	.69	.74	.71	.68	.67
10.0	.75	.70	.67	.74	.70	.67	.73	.69	.67	.73	.69	.66	.72	.69	.66	.65



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

r c c	80%			70%			50%			30%			10%			0
r w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r f c	20%			20%			20%			20%			20%			0
R C R	R C R:Room Cavity Ratio Wall Exitance Coefficients(W E C)															
0.0																
1.0	.160	.091	.029	.154	.088	.028	.141	.081	.026	.130	.075	.024	.119	.069	.022	
2.0	.150	.082	.025	.145	.080	.025	.134	.075	.023	.125	.070	.022	.116	.066	.021	
3.0	.140	.075	.022	.136	.073	.022	.127	.069	.021	.119	.065	.020	.111	.062	.019	
4.0	.132	.068	.020	.128	.067	.020	.120	.064	.019	.113	.061	.018	.107	.058	.018	
5.0	.124	.063	.018	.120	.062	.018	.114	.059	.017	.108	.057	.017	.102	.055	.016	
6.0	.117	.059	.017	.114	.057	.017	.108	.055	.016	.103	.054	.016	.098	.052	.015	
7.0	.111	.055	.015	.108	.054	.015	.103	.052	.015	.099	.051	.015	.094	.049	.014	
8.0	.105	.051	.014	.103	.051	.014	.098	.049	.014	.094	.048	.014	.091	.047	.014	
9.0	.100	.048	.014	.098	.048	.013	.094	.047	.013	.091	.045	.013	.087	.044	.013	
10.0	.096	.046	.013	.094	.045	.013	.090	.044	.012	.087	.043	.012	.084	.042	.012	

r c c	80%			70%			50%			30%			10%			0
r w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r f c	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.153	.133	.115	.131	.114	.100	.090	.079	.069	.052	.046	.041	.017	.015	.013	
3.0	.140	.113	.093	.120	.098	.080	.082	.068	.056	.047	.040	.033	.015	.013	.011	
4.0	.128	.098	.076	.110	.085	.066	.075	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.118	.086	.063	.101	.075	.055	.070	.052	.039	.040	.031	.023	.013	.010	.008	
6.0	.109	.077	.053	.094	.066	.046	.065	.046	.033	.038	.027	.019	.012	.009	.006	
7.0	.102	.069	.045	.088	.060	.039	.061	.042	.028	.035	.025	.017	.011	.008	.006	
8.0	.096	.062	.039	.082	.054	.034	.057	.038	.024	.033	.022	.014	.011	.007	.005	
9.0	.090	.057	.034	.078	.049	.030	.054	.035	.021	.031	.020	.013	.010	.007	.004	
10.0	.085	.052	.030	.073	.045	.026	.051	.032	.018	.030	.019	.011	.010	.006	.004	

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm											
NAME: 6506-10W-2700K						TYPE:室内			WEIGHT:		
SPEC.:						DIM.: 82*82*75mm			SERIAL No.:01		
MFR.: NORDECOR						SUR.:			Shielding Angle:24°		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	3H	3.8	4.5	4.0	4.7	4.9	5.8	6.6	6.0	6.7	6.9
	3H	4.7	5.5	5.0	5.7	5.9	7.1	7.9	7.4	8.0	8.2
	4H	5.1	5.8	5.3	6.0	6.2	7.6	8.3	7.9	8.5	8.8
	6H	5.3	6.0	5.6	6.2	6.4	7.7	8.4	8.0	8.6	8.8
	8H	5.4	6.0	5.7	6.3	6.5	7.7	8.3	8.0	8.5	8.8
	12H	5.5	6.1	5.8	6.3	6.6	7.6	8.2	7.9	8.5	8.8
4H	2H	4.5	5.2	4.8	5.4	5.6	6.2	6.9	6.4	7.1	7.3
	3H	5.7	6.3	6.0	6.5	6.8	7.7	8.3	8.0	8.6	8.8
	4H	6.1	6.6	6.4	6.9	7.2	8.3	8.9	8.7	9.2	9.5
	6H	6.4	6.9	6.8	7.2	7.6	8.4	8.9	8.8	9.2	9.6
	8H	6.5	6.9	6.9	7.3	7.7	8.4	8.8	8.7	9.2	9.5
	12H	6.6	7.0	7.0	7.4	7.7	8.3	8.7	8.7	9.1	9.5
8H	4H	6.5	6.9	6.8	7.3	7.6	8.4	8.9	8.8	9.3	9.6
	6H	6.9	7.3	7.3	7.7	8.1	8.6	8.9	9.0	9.3	9.7
	8H	7.0	7.4	7.5	7.8	8.2	8.5	8.8	8.9	9.2	9.7
	12H	7.2	7.5	7.6	7.9	8.4	8.4	8.7	8.9	9.2	9.6
12H	4H	6.4	6.8	6.8	7.2	7.6	8.4	8.8	8.8	9.2	9.6
	6H	6.9	7.2	7.3	7.6	8.1	8.5	8.9	9.0	9.3	9.7
	8H	7.0	7.3	7.5	7.8	8.2	8.5	8.8	8.9	9.2	9.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.8 / - 0.6					
1.5H	+ 0.2 / - 0.4					+ 1.8 / - 0.6					
2.0H	+ 0.5 / - 0.5					+ 0.4 / - 0.6					

CIE Pub.117, 560.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.0)
Area: 0.1 m2

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	86	80	76	86	80	76	85	79	76	72
0.80	94	88	84	93	87	84	92	87	83	80
1.00	98	92	89	97	92	88	96	92	88	84
1.25	102	97	93	101	96	93	99	95	92	88
1.50	105	100	97	104	99	96	102	98	95	90
2.00	108	104	100	106	102	99	104	100	98	93
2.50	110	106	103	108	104	102	105	102	100	94
3.00	111	108	105	110	106	104	106	104	102	95
4.00	113	111	108	111	109	107	108	106	104	97
5.00	115	112	111	113	111	109	109	107	106	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.300m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°




H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.300m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

Flux out:230.3 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.300m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.33V I:0.0930A P:9.6751W PF:0.4720 Freq:50.00Hz Lamp Flux:560.193x1 lm		
NAME: 6506-10W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°


AvgL	cd/m2
L_0~180(65)av	232
L_0~180(75)av	186
L_0~180(85)av	183
L_90~270(65)av	266
L_90~270(75)av	188
L_90~270(85)av	0
L_45(65)av	233
L_45(75)av	188
L_45(85)av	0

Standard: GB/T 29293-2012

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-08-16

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.300m [K=1.0000]
 Remarks:

Planar Illuminance Curve



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.300m [K=1.0000]
Remarks:

