


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

DATA OF LAMP		PHOTOMETRIC DATA Eff: 87.90 lm/W			
MODEL		I _{max} (cd)	2992	S/MH(C0/180)	0.42
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	0.39
RATED VOLTAGE(V)	85-265V	TOTAL FLUX(lm)	859.94	h UP, DN(C0-180)	0.0,51.3
NOMINAL FLUX(lm)	859.94	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0,48.7
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	220	h down(%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H_b Range: -90 - 90DEG
H_b Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum, lamp
10	1611	1725	1860	1609	1938	1534	1675	1622	0- 10	207.4	207.4	24.1, 24.1
20	438.0	578.5	495.0	528.7	546.2	509.3	456.9	536.8	10- 20	266.8	474.2	55.1, 55.1
30	338.6	335.5	342.6	332.0	356.8	324.3	347.5	328.7	20- 30	183.3	657.5	76.5, 76.5
40	69.57	109.0	130.7	147.5	141.6	117.1	86.32	78.66	30- 40	149.0	806.4	93.8, 93.8
50	14.49	14.97	20.05	18.00	19.46	14.32	14.40	12.34	40- 50	34.49	840.9	97.8, 97.8
60	6.089	6.526	9.505	7.791	9.154	5.929	5.497	4.843	50- 60	9.982	850.9	99, 99
70	3.322	3.195	4.082	3.781	4.692	3.337	3.397	2.865	60- 70	4.609	855.5	99.5, 99.5
80	2.786	2.411	2.702	2.634	3.362	2.674	2.811	2.448	70- 80	3.129	858.7	99.9, 99.9
90	2.175	0	0	0	2.158	0	0	0	80- 90	1.284	859.9	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

Conical surface Flux(90deg): 830.74 lm

%lum = 96.6%

%lamp = 96.6%

Conical surface Flux(120deg): 850.92 lm

%lum = 99.0%


%lamp = 99.0%

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-09-08

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	270	0
80	160	156
75	116	131
70	97	119
65	93	161
60	122	190
55	173	260
50	225	312
45	293	1066


H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

r CC	80%			70%			50%			30%			10%			0
r W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.11	1.09	1.07	1.09	1.07	1.05	1.05	1.04	1.02	1.02	1.00	.99	.98	.97	.96	.95
2.0	1.05	1.01	.98	1.03	.99	.97	.99	.97	.95	.97	.95	.93	.94	.92	.91	.89
3.0	.99	.94	.90	.97	.93	.90	.95	.91	.88	.92	.89	.87	.90	.88	.86	.84
4.0	.93	.88	.84	.92	.87	.84	.90	.86	.83	.88	.85	.82	.86	.83	.81	.80
5.0	.88	.83	.79	.87	.83	.79	.86	.81	.78	.84	.80	.78	.83	.79	.77	.76
6.0	.84	.79	.75	.83	.78	.75	.82	.77	.74	.80	.77	.74	.79	.76	.73	.72
7.0	.80	.75	.71	.79	.74	.71	.78	.74	.70	.77	.73	.70	.76	.72	.70	.68
8.0	.76	.71	.68	.76	.71	.67	.75	.70	.67	.74	.70	.67	.73	.69	.67	.65
9.0	.73	.68	.64	.73	.68	.64	.72	.67	.64	.71	.67	.64	.70	.66	.64	.63
10.0	.70	.65	.62	.70	.65	.62	.69	.65	.61	.68	.64	.61	.68	.64	.61	.60



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

r _{CC}	80%			70%			50%			30%			10%			0
r _W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.165	.094	.030	.158	.090	.029	.146	.084	.027	.134	.077	.025	.123	.072	.023	
2.0	.156	.085	.026	.150	.083	.025	.140	.078	.024	.130	.073	.023	.121	.069	.022	
3.0	.147	.078	.023	.142	.076	.023	.133	.072	.022	.125	.069	.021	.118	.065	.020	
4.0	.139	.072	.021	.135	.071	.021	.127	.068	.020	.120	.065	.020	.114	.062	.019	
5.0	.132	.067	.019	.128	.066	.019	.122	.063	.019	.116	.061	.018	.110	.059	.018	
6.0	.125	.063	.018	.122	.062	.018	.116	.060	.017	.111	.058	.017	.106	.056	.017	
7.0	.119	.059	.017	.117	.058	.017	.112	.056	.016	.107	.055	.016	.102	.053	.016	
8.0	.114	.056	.016	.111	.055	.016	.107	.053	.015	.103	.052	.015	.099	.051	.015	
9.0	.109	.053	.015	.107	.052	.015	.103	.051	.014	.099	.050	.014	.095	.048	.014	
10.0	.104	.050	.014	.102	.049	.014	.099	.048	.014	.095	.047	.013	.092	.046	.013	

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.146	.135	.126	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.154	.133	.114	.132	.114	.099	.090	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.141	.113	.092	.121	.098	.079	.083	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.130	.099	.075	.111	.085	.065	.077	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.120	.087	.062	.103	.075	.054	.071	.052	.038	.041	.031	.023	.013	.010	.007	
6.0	.112	.077	.052	.097	.067	.045	.067	.047	.032	.039	.028	.019	.012	.009	.006	
7.0	.105	.069	.044	.091	.060	.038	.063	.042	.027	.036	.025	.016	.012	.008	.005	
8.0	.099	.063	.038	.085	.055	.033	.059	.038	.023	.034	.023	.014	.011	.007	.005	
9.0	.094	.058	.033	.081	.050	.029	.056	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.089	.053	.029	.077	.046	.025	.053	.032	.018	.031	.019	.011	.010	.006	.004	

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm											
NAME: 6507						TYPE:10W-2700K			WEIGHT:		
SPEC.:						DIM.: 82*82*75mm			SERIAL No.:01		
MFR.: NORDECOR						SUR.:			Shielding Angle:24°		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	7.1	7.9	7.3	8.1	8.2	7.7	8.5	7.9	8.7	8.8	
	3H	7.0	7.7	7.2	7.9	8.1	7.6	8.4	7.9	8.6	8.8
	4H	6.9	7.6	7.2	7.9	8.1	7.6	8.3	7.9	8.5	8.8
	6H	6.9	7.6	7.2	7.8	8.1	7.6	8.3	7.9	8.5	8.7
	8H	6.9	7.6	7.2	7.8	8.1	7.6	8.2	7.9	8.5	8.7
	12H	6.9	7.6	7.2	7.8	8.1	7.5	8.2	7.8	8.4	8.7
4H	2H	6.9	7.6	7.1	7.8	8.0	7.5	8.2	7.7	8.4	8.6
	3H	6.8	7.4	7.1	7.7	7.9	7.4	8.1	7.7	8.3	8.6
	4H	6.7	7.3	7.1	7.6	7.9	7.4	8.0	7.8	8.3	8.6
	6H	6.7	7.2	7.1	7.6	7.9	7.4	8.0	7.8	8.3	8.6
	8H	6.8	7.2	7.1	7.6	7.9	7.4	7.9	7.8	8.3	8.6
	12H	6.8	7.2	7.2	7.6	8.0	7.4	7.8	7.8	8.2	8.6
8H	4H	6.6	7.1	7.0	7.5	7.8	7.3	7.8	7.7	8.1	8.5
	6H	6.7	7.1	7.1	7.5	7.9	7.4	7.8	7.8	8.2	8.6
	8H	6.7	7.1	7.2	7.5	7.9	7.4	7.7	7.8	8.2	8.6
	12H	6.9	7.2	7.3	7.6	8.1	7.4	7.6	7.8	8.1	8.6
12H	4H	6.6	7.0	7.0	7.4	7.8	7.3	7.7	7.7	8.1	8.5
	6H	6.7	7.0	7.1	7.4	7.9	7.4	7.7	7.8	8.1	8.6
	8H	6.7	7.0	7.2	7.5	8.0	7.4	7.7	7.8	8.1	8.6
Variations with the observer position at spacings:											
S = 1.0H	+ 2.7 / - 5.9					+ 2.6 / - 5.3					
1.5H	+ 5.1 / - 5.3					+ 4.5 / - 5.5					
2.0H	+ 2.0 / - 1.4					+ 5.8 / - 3.0					

CIE Pub.117, 859.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.5)
Area: 0.1 m2

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-09-08

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	88	81	78	87	81	78	86	81	77	74
0.80	95	89	86	94	89	85	93	88	85	81
1.00	99	94	90	99	93	90	97	93	90	86
1.25	103	98	95	102	98	94	100	96	94	89
1.50	106	101	98	105	101	98	103	99	96	92
2.00	109	105	101	107	103	101	105	101	99	94
2.50	110	107	104	109	105	103	106	103	101	95
3.00	112	108	106	110	107	105	107	104	102	96
4.00	114	111	109	112	109	107	108	106	105	98
5.00	115	113	111	113	111	109	109	108	106	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

H_b Range:-90 - 90DEG
H_b Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-09-08

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°




H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-09-08

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°

Flux out:255.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°



H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-09-08

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:150.11V I:0.1193A P:9.7833W PF:0.5462 Freq:50.00Hz Lamp Flux:859.94x1 lm		
NAME: 6507	TYPE:10W-2700K	WEIGHT:
SPEC.:	DIM.: 82*82*75mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:24°


AvgL	cd/m2
L_0~180(65)av	116
L_0~180(75)av	134
L_0~180(85)av	285
L_90~270(65)av	133
L_90~270(75)av	126
L_90~270(85)av	0
L_45(65)av	101
L_45(75)av	114
L_45(85)av	108

Standard: GB/T 29293-2012

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-09-08

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-09-08

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

