


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°

DATA OF LAMP		PHOTOMETRIC DATA Eff: 85.45 lm/W			
MODEL		I _{max} (cd)	1060	S/MH(C0/180)	0.60
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	0.43
RATED VOLTAGE(V)	85-265V	TOTAL FLUX(lm)	529.85	h UP, DN(C0-180)	0.0,57.2
NOMINAL FLUX(lm)	529.851	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0,42.8
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	220	h down(%)	100.0	CIBSE SHR MAX	0.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum, lamp
10	795.1	843.1	898.0	834.7	912.7	698.4	654.2	692.0	0- 10	84.99	84.99	16,16
20	334.5	503.8	634.8	456.0	438.9	321.2	364.6	318.7	10- 20	162.9	247.9	46.8, 46.8
30	221.4	249.8	268.2	240.4	256.0	182.2	189.0	168.8	20- 30	140.9	388.8	73.4, 73.4
40	38.64	120.4	131.9	121.4	70.07	35.06	70.38	26.95	30- 40	94.53	483.3	91.2, 91.2
50	8.719	16.38	45.12	31.99	13.63	9.208	8.650	10.94	40- 50	29.50	512.8	96.8, 96.8
60	4.925	5.269	7.796	8.079	6.982	4.158	3.848	7.495	50- 60	8.902	521.7	98.5, 98.5
70	3.295	3.003	4.863	4.086	3.760	2.482	2.644	5.713	60- 70	4.556	526.3	99.3, 99.3
80	2.509	1.713	0	2.119	2.469	1.435	0	2.890	70- 80	2.909	529.2	99.9, 99.9
90	1.255	0	0	0	1.290	0	0	0	80- 90	0.6409	529.9	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 503.83 lm

%lum = 95.1%

%lamp = 95.1%

Conical surface Flux(120deg): 521.75 lm

%lum = 98.5%


%lamp = 98.5%

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-08-24

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	238	0
80	144	0
75	111	133
70	96	142
65	92	153
60	98	156
55	113	466
50	136	702
45	166	908


H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°

r CC	80%			70%			50%			30%			10%			0
r W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.11	1.08	1.06	1.09	1.07	1.05	1.05	1.03	1.01	1.01	.98	.98	.98	.96	.95	.94
2.0	1.03	.99	.96	1.02	.98	.95	.98	.96	.93	.95	.93	.91	.93	.91	.89	.87
3.0	.97	.92	.88	.95	.91	.87	.93	.89	.86	.90	.87	.85	.88	.86	.83	.82
4.0	.91	.85	.81	.90	.85	.81	.88	.83	.80	.86	.82	.79	.84	.81	.78	.77
5.0	.85	.80	.76	.85	.79	.75	.83	.78	.75	.81	.77	.74	.80	.76	.73	.72
6.0	.81	.75	.71	.80	.74	.71	.78	.74	.70	.77	.73	.70	.76	.72	.69	.68
7.0	.76	.71	.67	.76	.70	.66	.74	.70	.66	.73	.69	.66	.72	.68	.65	.64
8.0	.72	.67	.63	.72	.66	.63	.71	.66	.62	.70	.65	.62	.69	.65	.62	.61
9.0	.69	.63	.59	.68	.63	.59	.67	.62	.59	.66	.62	.59	.66	.62	.59	.57
10.0	.65	.60	.56	.65	.60	.56	.64	.59	.56	.64	.59	.56	.63	.59	.56	.55



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°

r c c	80%			70%			50%			30%			10%			0
r w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r f c	20%			20%			20%			20%			20%			0
R C R	R C R:Room Cavity Ratio Wall Exitance Coefficients(W E C)															
0.0																
1.0	.176	.100	.032	.169	.096	.031	.157	.090	.029	.145	.084	.027	.134	.078	.025	
2.0	.167	.092	.028	.162	.089	.027	.151	.084	.026	.141	.079	.025	.132	.075	.024	
3.0	.159	.084	.025	.154	.082	.025	.145	.078	.024	.136	.075	.023	.129	.071	.022	
4.0	.150	.078	.023	.146	.077	.023	.138	.073	.022	.131	.070	.021	.125	.068	.021	
5.0	.143	.073	.021	.139	.071	.021	.132	.069	.020	.126	.067	.020	.120	.064	.019	
6.0	.136	.068	.019	.133	.067	.019	.127	.065	.019	.121	.063	.019	.116	.061	.018	
7.0	.129	.064	.018	.127	.063	.018	.121	.061	.018	.117	.060	.017	.112	.058	.017	
8.0	.124	.060	.017	.121	.060	.017	.116	.058	.017	.112	.057	.016	.108	.055	.016	
9.0	.118	.057	.016	.116	.057	.016	.112	.055	.016	.108	.054	.015	.104	.053	.015	
10.0	.113	.054	.015	.111	.054	.015	.107	.053	.015	.104	.052	.015	.101	.051	.015	

r c c	80%			70%			50%			30%			10%			0
r w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r f c	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.156	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.143	.114	.090	.123	.098	.078	.084	.068	.055	.049	.040	.032	.016	.013	.011	
4.0	.132	.099	.073	.114	.085	.063	.078	.059	.045	.045	.035	.026	.015	.011	.009	
5.0	.124	.087	.060	.106	.075	.052	.073	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.116	.078	.050	.100	.067	.044	.069	.047	.031	.040	.028	.018	.013	.009	.006	
7.0	.109	.070	.043	.094	.061	.037	.065	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.103	.064	.037	.089	.055	.032	.062	.039	.023	.036	.023	.013	.012	.008	.004	
9.0	.098	.059	.032	.085	.051	.028	.059	.036	.020	.034	.021	.012	.011	.007	.004	
10.0	.093	.054	.028	.081	.047	.024	.056	.033	.017	.033	.020	.010	.011	.006	.003	

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm										
NAME: 6593-7W-2700K						TYPE:室内			WEIGHT:	
SPEC.:						DIM.: 58*58*510mm			SERIAL No.:01	
MFR.: NORDECOR						SUR.:			Shielding Angle:36°	
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	8.2	9.1	8.4	9.3	9.4	10.5	11.4	10.7	11.6	11.7
	3H	8.1	8.9	8.3	9.1	9.3	10.4	11.3	10.7	11.5
	4H	8.1	8.9	8.4	9.1	9.3	10.4	11.2	10.7	11.4
	6H	8.1	8.9	8.4	9.1	9.3	10.3	11.1	10.6	11.3
	8H	8.1	8.9	8.4	9.1	9.4	10.3	11.0	10.6	11.3
	12H	8.2	8.9	8.5	9.2	9.4	10.2	10.9	10.6	11.2
4H	2H	8.0	8.8	8.3	9.0	9.2	10.3	11.1	10.5	11.3
	3H	7.9	8.6	8.2	8.9	9.2	10.2	10.9	10.5	11.2
	4H	7.9	8.6	8.3	8.9	9.2	10.2	10.9	10.6	11.2
	6H	8.0	8.6	8.4	8.9	9.2	10.2	10.7	10.5	11.1
	8H	8.1	8.6	8.5	8.9	9.3	10.1	10.6	10.5	11.0
	12H	8.2	8.7	8.6	9.0	9.4	10.1	10.5	10.5	10.9
8H	4H	7.9	8.4	8.3	8.7	9.1	10.1	10.6	10.5	11.0
	6H	8.0	8.4	8.4	8.8	9.2	10.1	10.5	10.5	10.9
	8H	8.1	8.5	8.6	8.9	9.4	10.0	10.4	10.5	10.8
	12H	8.3	8.6	8.8	9.1	9.5	9.9	10.3	10.4	10.7
12H	4H	7.8	8.3	8.2	8.7	9.0	10.1	10.6	10.5	10.9
	6H	8.0	8.3	8.4	8.7	9.2	10.0	10.4	10.5	10.8
	8H	8.1	8.4	8.6	8.8	9.3	10.0	10.3	10.4	10.7
Variations with the observer position at spacings:										
S = 1.0H	+ 3.0 / - 5.5					+ 2.2 / - 5.8				
1.5H	+ 5.2 / - 5.1					+ 4.1 / - 7.3				
2.0H	+ 2.3 / - 1.0					+ 5.4 / - 4.3				

CIE Pub.117, 529.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.2)
Area: 0.1 m2

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	86	79	76	86	79	75	85	79	75	72
0.80	94	88	84	93	87	84	92	87	83	79
1.00	98	93	89	97	92	88	96	92	88	84
1.25	102	97	93	101	97	93	99	95	92	88
1.50	105	100	97	104	100	96	102	98	95	91
2.00	108	104	100	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	111	108	105	110	106	104	106	104	102	95
4.00	114	111	108	111	109	107	108	106	104	97
5.00	115	112	111	113	111	109	109	107	106	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-24

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.000m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°




H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°

Flux out:199.3 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.26V I:0.0610A P:6.2009W PF:0.4619 Freq:50.00Hz Lamp Flux:529.851x1 lm		
NAME: 6593-7W-2700K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 58*58*510mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:36°


AvgL	cd/m2
L_0~180(65)av	107
L_0~180(75)av	112
L_0~180(85)av	235
L_90~270(65)av	114
L_90~270(75)av	106
L_90~270(85)av	0
L_45(65)av	113
L_45(75)av	122
L_45(85)av	0

Standard: GB/T 29293-2012

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-08-24

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



H_b Range: -90 - 90DEG
H_b Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-24

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.000m [K=1.0000]
Remarks:

