


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°

DATA OF LAMP		PHOTOMETRIC DATA Eff: 50.51 lm/W			
MODEL		I _{max} (cd)	162.4	S/MH(C0/180)	0.55
NOMINAL POWER(W)	1	LOR(%)	100.0	S/MH(C90/270)	0.55
RATED VOLTAGE(V)	85-265V	TOTAL FLUX(lm)	59.928	h UP, DN(C0-180)	0.0,45.0
NOMINAL FLUX(lm)	59.9282	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0,55.0
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	220	h down(%)	100.0	CIBSE SHR MAX	0.50



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum, lamp
10	103.7	99.19	97.44	104.0	133.6	113.7	114.8	110.0	0- 10	12.31	12.31	20.5, 20.5
20	40.30	41.76	47.07	42.36	58.65	53.17	68.39	57.13	10- 20	20.92	33.23	55.4, 55.4
30	11.48	12.40	10.37	15.96	19.69	21.61	22.35	19.71	20- 30	14.21	47.43	79.2, 79.2
40	3.541	3.320	5.243	4.017	5.304	5.631	9.396	4.754	30- 40	6.136	53.57	89.4, 89.4
50	2.074	2.075	2.318	2.323	2.373	2.387	2.455	2.197	40- 50	2.565	56.14	93.7, 93.7
60	1.430	1.424	1.594	1.543	1.643	1.454	1.527	1.415	50- 60	1.647	57.78	96.4, 96.4
70	0.8640	0.9425	1.069	0.9726	0.9417	0.8842	1.002	0.8604	60- 70	1.195	58.98	98.4, 98.4
80	0.6432	0.5457	0	0.5524	0.6725	0.5062	0	0.5151	70- 80	0.7737	59.75	99.7, 99.7
90	0.5281	0	0	0	0.5186	0	0	0	80- 90	0.1772	59.93	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

Conical surface Flux(90deg): 55.107 lm

%lum = 92.0%

%lamp = 92.0%

Conical surface Flux(120deg): 57.783 lm

%lum = 96.4%


%lamp = 96.4%

H_(b) Range: -90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 7.500m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	63	0
80	37	0
75	29	31
70	25	31
65	26	32
60	29	32
55	31	34
50	32	36
45	36	38


H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.500m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°

r CC	80%			70%			50%			30%			10%			0
r W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.11	1.08	1.06	1.09	1.06	1.04	1.05	1.03	1.01	1.01	.99	.98	.97	.96	.95	.94
2.0	1.04	.90	.96	1.02	.98	.95	.99	.96	.93	.96	.93	.91	.93	.91	.89	.88
3.0	.97	.92	.89	.96	.91	.88	.93	.90	.87	.91	.88	.85	.89	.86	.84	.82
4.0	.92	.86	.82	.91	.86	.82	.88	.84	.81	.86	.83	.80	.85	.82	.79	.78
5.0	.87	.81	.77	.86	.81	.77	.84	.80	.76	.82	.79	.76	.81	.78	.75	.74
6.0	.82	.77	.73	.82	.76	.73	.80	.76	.72	.79	.75	.72	.78	.74	.71	.70
7.0	.78	.73	.69	.78	.73	.69	.77	.72	.69	.75	.71	.68	.74	.71	.68	.67
8.0	.75	.69	.66	.74	.69	.66	.73	.69	.65	.72	.68	.65	.71	.68	.65	.64
9.0	.72	.66	.63	.71	.66	.63	.70	.66	.62	.69	.65	.62	.69	.65	.62	.61
10.0	.69	.64	.60	.68	.63	.60	.68	.63	.60	.67	.63	.60	.66	.62	.60	.58



H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
R _{CR}	R _{CR} :Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.177	.101	.032	.170	.097	.031	.158	.090	.029	.146	.084	.027	.135	.078	.025	
2.0	.166	.091	.028	.161	.089	.027	.150	.083	.026	.140	.079	.025	.131	.074	.023	
3.0	.156	.083	.025	.151	.081	.024	.142	.077	.023	.134	.073	.022	.126	.070	.022	
4.0	.146	.076	.022	.142	.074	.022	.135	.071	.021	.127	.068	.021	.121	.066	.020	
5.0	.138	.070	.020	.134	.069	.020	.128	.066	.020	.121	.064	.019	.116	.062	.019	
6.0	.130	.065	.019	.127	.064	.018	.121	.062	.018	.116	.060	.018	.111	.058	.017	
7.0	.123	.061	.017	.121	.060	.017	.116	.058	.017	.111	.057	.017	.106	.055	.016	
8.0	.117	.057	.016	.115	.057	.016	.110	.055	.016	.106	.054	.016	.102	.052	.015	
9.0	.112	.054	.015	.110	.053	.015	.106	.052	.015	.102	.051	.015	.098	.050	.014	
10.0	.107	.051	.014	.105	.051	.014	.101	.050	.014	.098	.049	.014	.095	.048	.014	

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.156	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.142	.114	.090	.122	.098	.078	.084	.068	.055	.048	.040	.032	.016	.013	.011	
4.0	.131	.099	.074	.113	.085	.064	.078	.059	.045	.045	.035	.027	.014	.011	.009	
5.0	.122	.087	.061	.105	.075	.053	.072	.053	.037	.042	.031	.022	.013	.010	.007	
6.0	.114	.077	.051	.098	.067	.045	.068	.047	.032	.039	.028	.019	.013	.009	.006	
7.0	.107	.070	.043	.092	.060	.038	.064	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.101	.063	.037	.087	.055	.033	.060	.038	.023	.035	.023	.014	.011	.007	.005	
9.0	.095	.058	.033	.082	.050	.028	.057	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.090	.053	.029	.078	.046	.025	.054	.033	.018	.032	.019	.011	.010	.006	.004	

H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.500m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm											
NAME: 6965-1W-3000K					TYPE:室内			WEIGHT:			
SPEC.:					DIM.: 32*32*125mm			SERIAL No.:01			
MFR.: NORDECOR					SUR.:			Shielding Angle:30°			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	5.1	6.0	5.4	6.2	6.3	5.6	6.5	5.9	6.7	6.8	
	3H	6.3	7.1	6.5	7.3	7.5	7.0	7.8	7.3	8.0	8.2
	4H	7.0	7.7	7.2	8.0	8.2	7.7	8.5	8.0	8.7	8.9
	6H	7.8	8.5	8.1	8.8	9.0	7.8	8.5	8.1	8.7	9.0
	8H	8.3	9.0	8.6	9.3	9.5	7.7	8.4	8.0	8.7	8.9
	12H	8.9	9.6	9.2	9.9	10.1	7.7	8.4	8.0	8.6	8.9
4H	2H	5.6	6.4	5.9	6.6	6.8	6.0	6.8	6.3	7.0	7.2
	3H	7.0	7.7	7.4	8.0	8.3	7.7	8.3	8.0	8.6	8.9
	4H	7.9	8.5	8.3	8.8	9.1	8.5	9.1	8.9	9.4	9.7
	6H	9.0	9.5	9.3	9.8	10.2	8.7	9.2	9.0	9.5	9.9
	8H	9.6	10.1	10.0	10.5	10.8	8.6	9.1	9.0	9.5	9.8
	12H	10.3	10.8	10.7	11.2	11.6	8.6	9.0	9.0	9.4	9.8
8H	4H	8.3	8.8	8.7	9.2	9.6	8.8	9.3	9.2	9.7	10.1
	6H	9.6	10.1	10.1	10.5	10.9	9.0	9.4	9.5	9.8	10.3
	8H	10.5	10.8	10.9	11.2	11.7	9.0	9.3	9.4	9.8	10.2
	12H	11.4	11.7	11.9	12.2	12.7	8.9	9.2	9.4	9.7	10.1
12H	4H	8.3	8.8	8.7	9.1	9.5	8.9	9.4	9.3	9.7	10.1
	6H	9.6	10.0	10.1	10.4	10.9	9.1	9.5	9.5	9.9	10.3
	8H	10.5	10.8	10.9	11.2	11.7	9.0	9.4	9.5	9.8	10.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.3					+ 0.5 / - 0.5					
1.5H	+ 0.2 / - 0.2					+ 1.2 / - 0.5					
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.5					

CIE Pub.117, 59.93 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -9.8)
Area: 0.1 m2

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	85	78	74	85	78	74	84	78	74	70
0.80	93	86	82	92	86	82	91	85	82	78
1.00	97	91	87	96	91	87	95	91	86	82
1.25	101	96	92	100	95	92	98	94	91	86
1.50	104	99	95	103	98	95	101	97	94	89
2.00	107	103	99	106	102	98	103	100	97	91
2.50	109	105	102	107	104	101	104	101	99	93
3.00	111	107	104	109	106	103	106	103	101	94
4.00	113	110	108	111	108	106	107	105	104	96
5.00	114	112	110	112	110	108	108	107	105	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

H_b) Range:-90 - 90DEG
H_b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°




H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°

Flux out:23.06 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H_(b) Range:-90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2026-08-16

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:7.500m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°



H_(b) Range: -90 - 90DEG
H_(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.500m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.31V I:0.0130A P:1.1864W PF:0.4128 Freq:50.00Hz Lamp Flux:59.9282x1 lm		
NAME: 6965-1W-3000K	TYPE:室内	WEIGHT:
SPEC.:	DIM.: 32*32*125mm	SERIAL No.:01
MFR.: NORDECOR	SUR.:	Shielding Angle:30°


AvgL	cd/m2
L_0~180(65)av	28
L_0~180(75)av	30
L_0~180(85)av	65
L_90~270(65)av	31
L_90~270(75)av	30
L_90~270(85)av	0
L_45(65)av	27
L_45(75)av	30
L_45(85)av	0

Standard: GB/T 29293-2012

H_(b) Range:-90 - 90DEG
 H_(b) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2026-08-16

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:7.500m [K=1.0000]
 Remarks:

Planar Illuminance Curve



H(b) Range: -90 - 90DEG
H(b) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2026-08-16

V(B) Range: -75 - 75DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 7.500m [K=1.0000]
Remarks:

