

Report No.:

Test Time: 2026-05-18 10:42

Luminaire Property

Luminaire Manufacturer: NORDECOR
Luminaire Description: 80088
Luminous Width (mm): 52
Current: 0.056 A
Power Factor: 0.459


Luminous Length (mm): 52
Voltage: 220.3 V
Power: 5.72 W

Photometric Results


CIE Class: Direct
Measurement Flux: 436.1 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(10%,50%,80%,100%): H78.7,H50.3,H32.3,H2
Vertical Diffuse Angle(10%,50%,80%,100%): V81.1,V50,V31.7,V2
Luminaire Efficacy Rating (LER): 76.30
Max. Intensity: 590.98 cd
S/MH(C0/C180): 0.80

Total Rated Lamp Lumens: 436.1 lm
Efficiency: 100%
Upward Ratio: 0%
Central Intensity: 589.35 cd
Pos of Max. Intensity: H180 V2
S/MH(C90/C270): 0.79

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd



Average Diffuse Angle(50%): 50.1°

— C0-C180 — C90-C270 — G2

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)




C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	101	100	99	98	97	96	95	93
2	108	103	99	95	105	101	97	94	98	95	92	95	92	90	92	90	88	86
3	102	96	91	87	100	95	90	86	92	88	85	89	86	84	87	85	82	81
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	79	77	75
5	93	84	79	74	91	83	78	74	82	77	73	80	76	73	78	75	72	71
6	88	79	74	69	87	79	73	69	77	72	69	76	71	68	74	71	68	66
7	84	75	69	65	83	74	69	65	73	68	64	72	67	64	71	67	64	62
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	77	67	61	57	76	67	61	57	66	61	57	65	60	57	64	60	57	56
10	73	64	58	54	72	63	58	54	63	58	54	62	57	54	61	57	54	53


Spacing Criteria (0-180): 0.80
Spacing Criteria (90-270): 0.79
Spacing Criteria (Diagonal): 0.78



C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Isocandela (rectangle)




Imax (100%): 591 cd

(10%):	59 cd	(16%):	95 cd
(25%):	148 cd	(40%):	236 cd
(63%):	372 cd	(100%):	591 cd

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:


Isocandela (sphere)



Imax (100%): 591 cd

(10%):	59 cd	(16%):	95 cd
(25%):	148 cd	(40%):	236 cd
(63%):	372 cd	(100%):	591 cd

IsoLux Plot



Mounting Height: 1.0m Max Lux(100%): 590.2 lx


(1%): 5.9 lx	(2%): 11.8 lx
(5%): 29.5 lx	(10%): 59.0 lx
(20%): 118.0 lx	(50%): 295.1 lx
(100%): 590.2 lx	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Roadway CU Curve

Efficiency(%)





C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	11966	5581	2805	2493	2546	3157	4187	6048	12008
C90	20052	12209	7505	4541	3063	3298	4287	6304	12433
C180	13352	6634	2972	2315	2476	2887	3844	5686	11117
C270	16935	10592	6789	3780	2739	3309	4301	6496	13196

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 8.443 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 589.3 lx


(1%): 5.9 lx	(2%): 11.8 lx
(5%): 29.5 lx	(10%): 58.9 lx
(20%): 117.9 lx	(50%): 294.7 lx
(100%): 589.3 lx	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



C Plane (°): 0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	16.2	17.1	16.5	17.3	17.5	17.2	18.0	17.4	18.2	18.4
3H	16.3	17.1	16.6	17.3	17.5	17.2	18.0	17.5	18.2	18.4
4H	16.4	17.1	16.7	17.4	17.7	17.3	18.0	17.6	18.3	18.5
6H	16.7	17.4	17.0	17.6	17.9	17.5	18.2	17.8	18.4	18.7
8H	16.9	17.6	17.3	17.9	18.2	17.7	18.4	18.0	18.7	19.0
12H	17.3	17.9	17.7	18.3	18.6	18.0	18.7	18.4	19.0	19.3
X=4H Y=2H	16.1	16.8	16.4	17.1	17.4	17.0	17.7	17.3	18.0	18.3
3H	16.2	16.9	16.6	17.2	17.5	17.1	17.7	17.5	18.0	18.3
4H	16.5	17.0	16.9	17.4	17.7	17.3	17.8	17.7	18.2	18.5
6H	17.0	17.5	17.4	17.8	18.2	17.7	18.2	18.1	18.6	18.9
8H	17.4	17.9	17.8	18.2	18.7	18.1	18.5	18.5	18.9	19.3
12H	18.0	18.4	18.5	18.8	19.3	18.6	19.0	19.1	19.4	19.9
X=8H Y=4H	16.6	17.0	17.0	17.4	17.8	17.3	17.8	17.7	18.2	18.6
6H	17.3	17.7	17.8	18.1	18.6	17.9	18.3	18.4	18.7	19.2
8H	17.9	18.2	18.4	18.7	19.2	18.5	18.8	19.0	19.3	19.7
12H	18.8	19.1	19.3	19.6	20.1	19.3	19.6	19.8	20.1	20.6
X=12H Y=4H	16.6	17.0	17.0	17.4	17.9	17.3	17.7	17.8	18.2	18.6
6H	17.4	17.8	17.9	18.2	18.7	18.0	18.4	18.5	18.8	19.3
8H	18.2	18.4	18.7	18.9	19.4	18.7	19.0	19.2	19.4	19.9
Variations with the observer position at spacings:										
S=1.0H	+3.3/-2.9					+2.8/-2.4				
S=1.5H	+5.6/-3.6					+5.2/-3.4				
S=2.0H	+7.4/-4.1					+7.0/-4.1				

Calculate in accordance with CIE Pub.117. The table is revised with 436lm ($8\log(F/F_0) = -2.9$).

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM


	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	213	48.8
	FL (0°-30°)	158	36.2
	FM (30°-60°)	50	11.5
	FH (60°-80°)	3	0.7
	FVH (80°-90°)	2	0.4
	BACK LIGHT	223	51.2
	BL (0°-30°)	165	37.9
	BM (30°-60°)	54	12.3
	BH (60°-80°)	3	0.7
	BVH (80°-90°)	2	0.4
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U0 G0

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

LCS Graph



Back Light

Forward Light

Scale= MAX LCS%

Trapped Light:NA,NA

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 8.443 m

Humidity:

Inspector:

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.83	0.90	0.95	0.98	1.02	1.04	1.06	1.09	1.10	
	0.30		0.78	0.86	0.90	0.94	0.98	1.01	1.03	1.06	1.08	
	0.20		0.75	0.82	0.87	0.90	0.95	0.99	1.01	1.04	1.06	
0.50	0.50	0.20	0.82	0.88	0.92	0.95	0.99	1.01	1.03	1.05	1.06	
	0.30		0.78	0.84	0.89	0.92	0.96	0.99	1.01	1.03	1.05	
	0.20		0.75	0.81	0.86	0.89	0.93	0.96	0.98	1.01	1.03	
0.30	0.50	0.20	0.81	0.87	0.90	0.93	0.96	0.98	1.00	1.01	1.03	
	0.30		0.77	0.83	0.87	0.90	0.94	0.96	0.98	1.00	1.01	
	0.20		0.74	0.81	0.85	0.88	0.92	0.94	0.96	0.99	1.00	
0.00	0.00	0.00	0.73	0.79	0.83	0.85	0.89	0.91	0.92	0.94	0.95	
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.61	0.49	0.41	0.35	0.28	0.23	0.20	0.15	0.13	
	0.30		0.51	0.42	0.36	0.31	0.25	0.21	0.18	0.14	0.12	
	0.20		0.43	0.36	0.32	0.28	0.23	0.20	0.17	0.14	0.11	
0.50	0.50	0.20	0.58	0.46	0.39	0.33	0.26	0.26	0.18	0.14	0.12	
	0.30		0.49	0.40	0.34	0.30	0.24	0.20	0.17	0.13	0.11	
	0.20		0.42	0.35	0.30	0.27	0.22	0.18	0.16	0.13	0.11	
0.30	0.50	0.20	0.55	0.44	0.36	0.31	0.24	0.20	0.17	0.13	0.11	
	0.30		0.47	0.38	0.33	0.28	0.22	0.19	0.16	0.12	0.10	
	0.20		0.41	0.34	0.29	0.26	0.21	0.17	0.15	0.12	0.10	
0.00	0.00	0.00	0.28	0.22	0.18	0.16	0.12	0.10	0.08	0.07	0.05	
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.13	0.15	0.16	0.17	0.18	0.19	0.19	0.20	0.21	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.19	0.19	
	0.20		0.06	0.08	0.10	0.11	0.13	0.14	0.15	0.17	0.18	
0.50	0.50	0.20	0.13	0.14	0.15	0.16	0.17	0.18	0.19	0.20	0.20	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.19	
	0.20		0.06	0.08	0.09	0.11	0.13	0.14	0.15	0.17	0.17	
0.30	0.50	0.20	0.12	0.14	0.15	0.15	0.17	0.17	0.18	0.19	0.19	
	0.30		0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.18	
	0.20		0.06	0.08	0.09	0.11	0.12	0.14	0.15	0.16	0.17	
0.00	0.00	0.00	NA	NA	NA	NA	NA	NA	NA	NA	NA	
Rating:6W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	587.9	0.6	0.6	0.13	0.13
1.0-2.0	587.1	1.7	2.2	0.39	0.52
2.0-3.0	585.4	2.8	5.0	0.64	1.16
3.0-4.0	583.0	3.9	9.0	0.89	2.05
4.0-5.0	579.9	5.0	13.9	1.14	3.20
5.0-6.0	575.8	6.1	20.0	1.39	4.58
6.0-7.0	570.6	7.1	27.1	1.62	6.21
7.0-8.0	564.6	8.1	35.2	1.85	8.06
8.0-9.0	557.6	9.0	44.2	2.07	10.13
9.0-10.0	549.8	10.0	54.1	2.28	12.41
10.0-11.0	540.6	10.8	64.9	2.48	14.89
11.0-12.0	530.4	11.6	76.5	2.66	17.55
12.0-13.0	519.4	12.3	88.9	2.83	20.38
13.0-14.0	506.9	13.0	101.8	2.98	23.35
14.0-15.0	493.3	13.5	115.4	3.11	26.46
15.0-16.0	478.7	14.0	129.4	3.22	29.67
16.0-17.0	462.9	14.4	143.8	3.31	32.98
17.0-18.0	446.5	14.7	158.6	3.38	36.36
18.0-19.0	428.6	14.9	173.5	3.42	39.77
19.0-20.0	410.0	15.0	188.5	3.44	43.22
20.0-21.0	391.0	15.0	203.5	3.44	46.66
21.0-22.0	370.4	14.9	218.4	3.41	50.07
22.0-23.0	349.8	14.7	233.1	3.37	53.44
23.0-24.0	329.0	14.4	247.4	3.30	56.74
24.0-25.0	307.6	14.0	261.4	3.21	59.94
25.0-26.0	286.9	13.5	275.0	3.11	63.05
26.0-27.0	265.5	13.0	288.0	2.98	66.03
27.0-28.0	244.4	12.4	300.3	2.84	68.86
28.0-29.0	224.5	11.7	312.1	2.69	71.56
29.0-30.0	204.3	11.0	323.1	2.53	74.09
30.0-31.0	185.3	10.3	333.4	2.36	76.45
31.0-32.0	167.1	9.6	343.0	2.20	78.65
32.0-33.0	149.8	8.8	351.8	2.02	80.67
33.0-34.0	134.3	8.1	360.0	1.86	82.54
34.0-35.0	119.2	7.4	367.4	1.70	84.23
35.0-36.0	105.3	6.7	374.1	1.54	85.77

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	93.0	6.1	380.1	1.39	87.16
37.0-38.0	81.5	5.4	385.6	1.25	88.41
38.0-39.0	71.5	4.9	390.5	1.12	89.53
39.0-40.0	62.5	4.4	394.8	1.00	90.53
40.0-41.0	54.5	3.9	398.7	0.89	91.42
41.0-42.0	47.6	3.5	402.2	0.79	92.21
42.0-43.0	41.4	3.1	405.2	0.70	92.91
43.0-44.0	36.0	2.7	408.0	0.62	93.54
44.0-45.0	31.8	2.4	410.4	0.56	94.10
45.0-46.0	28.0	2.2	412.6	0.50	94.60
46.0-47.0	24.8	2.0	414.6	0.45	95.05
47.0-48.0	21.8	1.8	416.3	0.40	95.46
48.0-49.0	18.9	1.6	417.9	0.36	95.81
49.0-50.0	16.4	1.4	419.2	0.31	96.13
50.0-51.0	14.1	1.2	420.4	0.27	96.40
51.0-52.0	12.0	1.0	421.5	0.24	96.64
52.0-53.0	10.4	0.9	422.4	0.21	96.84
53.0-54.0	9.2	0.8	423.2	0.19	97.03
54.0-55.0	8.2	0.7	423.9	0.17	97.20
55.0-56.0	7.3	0.7	424.6	0.15	97.35
56.0-57.0	6.5	0.6	425.2	0.14	97.49
57.0-58.0	5.8	0.5	425.7	0.12	97.61
58.0-59.0	5.2	0.5	426.2	0.11	97.72
59.0-60.0	4.7	0.4	426.6	0.10	97.82
60.0-61.0	4.2	0.4	427.0	0.09	97.92
61.0-62.0	3.8	0.4	427.4	0.08	98.00
62.0-63.0	3.6	0.3	427.8	0.08	98.08
63.0-64.0	3.3	0.3	428.1	0.07	98.15
64.0-65.0	3.2	0.3	428.4	0.07	98.23
65.0-66.0	3.1	0.3	428.7	0.07	98.30
66.0-67.0	3.0	0.3	429.0	0.07	98.37
67.0-68.0	3.0	0.3	429.3	0.07	98.44
68.0-69.0	3.0	0.3	429.6	0.07	98.51
69.0-70.0	2.9	0.3	429.9	0.07	98.57
70.0-71.0	2.9	0.3	430.2	0.07	98.64
71.0-72.0	2.9	0.3	430.5	0.07	98.71

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 8.443 m

Humidity:

Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G0.0	589.3	587.1	589.3	587.1	589.3					
G1.0	587.3	588.6	590.4	584.2	587.3					
G2.0	584.7	589.5	591.0	580.9	584.7					
G3.0	580.9	589.3	590.5	576.7	580.9					
G4.0	577.0	588.4	589.5	571.8	577.0					
G5.0	572.2	586.8	587.4	566.4	572.2					
G6.0	565.8	583.8	584.4	559.1	565.8					
G7.0	559.1	580.0	580.5	551.8	559.1					
G8.0	551.2	575.2	575.2	543.6	551.2					
G9.0	543.2	569.4	569.3	533.5	543.2					
G10.0	533.6	562.9	562.5	523.8	533.6					
G11.0	522.8	554.1	553.5	511.6	522.8					
G12.0	511.3	545.4	544.7	499.4	511.3					
G13.0	499.4	534.3	534.0	486.8	499.4					
G14.0	484.6	523.3	521.2	471.4	484.6					
G15.0	470.9	510.6	508.2	456.3	470.9					
G16.0	453.9	495.2	493.3	441.0	453.9					
G17.0	438.1	480.9	477.7	422.8	438.1					
G18.0	420.9	464.6	461.7	405.2	420.9					
G19.0	401.3	446.3	442.5	386.2	401.3					
G20.0	383.4	428.7	424.1	367.5	383.4					
G21.0	364.1	407.3	404.5	348.4	364.1					
G22.0	343.2	386.8	382.0	327.1	343.2					
G23.0	323.8	366.8	360.8	308.3	323.8					
G24.0	301.7	344.1	338.1	288.4	301.7					
G25.0	282.1	322.3	316.1	267.7	282.1					
G26.0	261.8	301.5	295.3	248.2	261.8					
G27.0	240.8	277.6	271.6	227.5	240.8					
G28.0	221.3	256.2	250.2	209.9	221.3					
G29.0	201.8	234.1	230.2	192.1	201.8					
G30.0	181.2	213.6	207.6	174.2	181.2					
G31.0	164.3	194.9	188.8	157.8	164.3					
G32.0	145.8	174.5	168.2	143.0	145.8					
G33.0	130.8	157.7	151.4	127.3	130.8					
G34.0	116.7	141.3	135.0	114.4	116.7					
G35.0	101.5	125.6	118.3	101.1	101.5					
G36.0	89.1	111.7	104.6	90.4	89.1					

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 8.443 m

Humidity:

Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C90.0	C180.0	C270.0	C360.0					
G37.0	77.4	98.7	91.6	80.5	77.4					
G38.0	66.7	87.7	78.3	71.3	66.7					
G39.0	57.7	78.3	68.2	63.7	57.7					
G40.0	49.0	69.2	57.8	56.5	49.0					
G41.0	41.8	61.6	49.6	50.2	41.8					
G42.0	35.6	55.0	42.1	45.0	35.6					
G43.0	30.1	48.2	35.2	39.8	30.1					
G44.0	26.0	43.1	29.8	36.0	26.0					
G45.0	22.9	38.3	25.5	32.4	22.9					
G46.0	19.8	34.2	22.2	29.0	19.8					
G47.0	17.1	30.6	19.5	26.0	17.1					
G48.0	14.3	27.1	16.5	23.0	14.3					
G49.0	11.9	24.1	13.8	20.6	11.9					
G50.0	9.7	21.2	11.5	18.4	9.7					
G51.0	7.8	18.5	9.1	16.2	7.8					
G52.0	6.4	16.3	7.4	14.5	6.4					
G53.0	5.4	14.4	6.1	13.2	5.4					
G54.0	4.8	12.9	5.2	11.8	4.8					
G55.0	4.3	11.6	4.6	10.5	4.3					
G56.0	4.0	10.3	4.0	9.2	4.0					
G57.0	3.8	9.2	3.7	8.1	3.8					
G58.0	3.6	8.0	3.4	7.0	3.6					
G59.0	3.5	7.0	3.3	6.0	3.5					
G60.0	3.4	6.1	3.1	5.1	3.4					
G61.0	3.2	5.4	3.0	4.4	3.2					
G62.0	3.1	4.8	2.9	3.8	3.1					
G63.0	3.0	4.3	2.8	3.5	3.0					
G64.0	2.9	3.8	2.9	3.3	2.9					
G65.0	2.9	3.5	2.8	3.1	2.9					
G66.0	2.9	3.3	2.8	3.1	2.9					
G67.0	2.9	3.1	2.8	3.1	2.9					
G68.0	3.0	3.0	2.8	3.2	3.0					
G69.0	2.9	3.1	2.8	3.1	2.9					
G70.0	2.9	3.0	2.7	3.1	2.9					
G71.0	2.9	3.0	2.7	3.0	2.9					
G72.0	3.0	3.0	2.7	3.0	3.0					
G73.0	3.0	3.0	2.7	2.9	3.0					

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 8.443 m

Humidity:

Inspector:

Unit: cd

Gamma Plane (°):0.0-90.0:1.0
Test Device: GPM-1600L
Distance: 8.443 m
Humidity:
Inspector: